



QP.MOHARE

General Description:

High quality water-based decorative paint, that gives the impression of coloring wavy, it is applicable on interior surface. And it is anti-fungal, bacterial and viruses on painted surfaces in accordance with JIS Z 2801, HGT 3950 standards.

Special properties:

- 1. Stylish and elegant.
- 2. Excellent adhesion strength.
- 3. Tintable.
- 4. Good open time.
- 5. Easy to use.
- 6. Easy to clean
- 7. Good Opacity.
- 8. Odorless, Mercury-free and Lead-free.
- 9. Environmentally friendly, non-toxic and non-flammable.
- 10. This product is anti-bacterial, fungal, viruses' development on applied paint coats.

Application:

- 1- Surfaces must be prepared by scraping and priming with diluted QP Bond.
- 2- Level surface using three layers of Silky Coat putty.
- 3- Apply one coat of QP Fine paint.
- 4- Apply one coat of Vinyl Matt white color.
- 5- Tint QP. MOHARE with a suitable color.
- 6- Apply one coat of Use special brush to paint QP. MOHARE in random way.
- 7- Apply QP. MOHARE in random way by Decorative trowel.

Application tools: Roll, Decorative brush., Decorative trowel.

Note:

- Don't mix QP MOHARE with any kind of liquid. Use it as it is.

رأس المال ٨٠٠ الف دينار اردني

شركة القدس لصناعات الدهانات المساهمة الخاصة المحدودة





- Donotapplyiftemperatureisbelow5° C

Package and Storage:

- 1kg, 4 kg in plastic container.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production.

Technical Data:

| Color | Multi-color |
|----------------------|---|
| Gloss | PEARL |
| Binder | Styrene Acrylic Copolymer |
| priming | Vinyl Matt white color |
| PH value | 7-9 |
| Opacity | 6-8 m ² /kg |
| Drying time | 24 hours, subject to temperature. According to standard |
| | specification ASTM D5895 |
| Solid Content | 60% |