

QP. Plastcoat

CEMENT BASE FINISH PLASTER

General description:

Decorative Cement Plaster (copolymer powder of vinyl acetate and ethylene) of high quality. It is known in the markets as "Spanish Plaster Finish". It is applicable to exterior surfaces. It meets European standard: EN 998-1

Special Features:

- Available in many colors (see catalogue), and resistant to UV light.
- Resistant to shrinkage and expansion resulting from the variations of temperature (-5 to +60°C) and from the humidity.
- Water repellent
- Easy to use.
- Odorless when applied.

Preparation of surface:

- Clean all foreign matter

Mixing:

- Put clean water (without chemical additives) in clean mixing container.
- Mix at a ratio of ± 3 kg powder to ± 1 liter of water.
- Stir by a hand or an electrical agitator the admixture well for 1 minute.
- Make sure that everything is mixed well.
- Wait for a 5 minutes period (settle-down) before using the admixture in the application.

Application:

- Apply number of coats based on surface condition and desired finish by using a stainless steel trowel used in finish-works. It is recommended that coat thickness should not exceed 0.5 cm.

Notes:

- It is advised to use a layer thickness between (0.3 -0.5) cm.
- Use all admixtures in the same day.
- It is advised not apply if below 5°C

Package & Storage:

- 20 kg in paper bags.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production.

Technical Data:

Color	Available in many colors (see color chart).
Physical State	Powder
Binder	Copolymer powder of vinyl acetate and ethylene
Filler	Fine graded fillers, cement, and other materials.
Specific density	1.7
Layer thickness	3-5 mm
Coverage	3 kg/m ² (thickness 3 mm)
Safety	Nontoxic and fire resistant.

European standard: EN 998-1

STANDARD			
LIMIT OF STANDARD	Compressive Strength	Adhesive Strength	Capillary Water Absorption
	0.4-2.5 N/mm ²	0.3 N/mm ² ≥	≤0.4 kg/m ²
CEMENT BASE FINISH PLASTER	0.4-2.5 N/mm ²	0.3 N/mm ² ≥	≤ 0.4 kg/m ²