QP. SEAL

Proof Coating

General Description:

QP.Seal is Styrene Acrylic Copolymer based reflecting paint for roof and exterior walls providing a flexible and high build coating layer. QP.Seal is waterproof coating.

Special Features:

- Easy to apply to all concrete surfaces.
- Weather-resistant
- Acrylic properties to insure high adhesion.
- High flexibility to avoid crack that a result of surface by temperature variations.
- Provides seamless coating.
- Water proof breather
- Odorless when applied.

Application steps:

1. **Preparation of surfaces:**
   - Clear from all oil, loose particles and all foreign matters
   - treat crack, holes with QP CRACK
2. **Priming:** It is recommended to prime specially if applied on old surfaces
3. **Application:**
   - Use roll, brush or spray machine to apply QP SEAL. (Two coats at least).
   - Apply as many coats as needed to reach desired thickness .Recommended thickness is 2mm
   - Consider drying time of 24 hours per each coat before applying next one.

Not:

- Ready to use Without dilution
- Do not apply if it is raining, surfaces must be dry.
- Do not apply if temperature is below 5 ˚c.

Package and Storage:

- 20 Kg in plastic drum.

- Must be stored unopened in dry conditions away from direct heat, or frost. Shelf-life is 12 months

Technical Data:

Color:	White
Binder:	Styrene Acrylic Copolymer
Specific density:	1.35
Consumption:	1.2 m²/kg subject to surface leveling at thickness up to 3 mm
Drying time:	3-8 hours
Recommended Thickness:	2 mm
Solid content:	55%