

## QP.MARMO

### General Description:

High quality water-based decorative putty (Vinyl acetate ethylene), it provides an attractive appearance of natural marble; it is applicable to interior surfaces only. And it is anti-fungal, bacterial and viruses on painted surfaces in accordance with JIS Z 2801, HGT 3950 standards.

### Special properties:

1. Stylish and elegant.
2. Excellent adhesion strength.
3. Tintable.
4. Good open time.
5. Easy to use.
6. Easy to clean.
7. Odorless, Mercury-free and Lead-free.
8. Environmentally friendly, non-toxic and non-flammable.
9. This product is anti-bacterial, fungal, viruses' development on applied paint coats.

### Application:

1. Surfaces must be prepared by scraping and priming with diluted QP Bond.
2. Level surface using two or three layers of Silky Coat putty.
3. Apply one coat using QP Fine.
4. Apply a second coat using Yellow Can vinyl matte colored with favorite color.
5. Choose suitable Marmo color.
6. Applying first layer of Marmo using a trowel.
7. Applying another layer of Marmo in random strokes, pressing until smooth to get the preferred glittering effect.
8. Consider drying time per coat.
9. Do not apply if temperature is below 5°C.

**Application tools:** Roller, brush, trowel, putty knife.

**Note:** Don't mix Marmo with any kind of liquid. Use it as it is.

### Package and Storage:

- 1kg, 5kg in plastic container.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production

### Technical Data:

<b>Color:</b>	<b>Multi-color</b>
<b>Gloss:</b>	<b>High gloss</b>
<b>Binder:</b>	<b>Vinyl Acetate Ethylene</b>
<b>Priming:</b>	<b>Yellow can vinyl matte emulsion</b>
<b>PH value:</b>	<b>7-9</b>
<b>Opacity:</b>	<b>4 - 6 m<sup>2</sup>/kg</b>
<b>Drying time:</b>	<b>24 hours, subject to temperature. According to ASTM D5895</b>
<b>Solid Content:</b>	<b>65%</b>