

## QP.LAMASAT

### General Description:

High quality water-based decorative paint (styrene acrylic copolymer), used to give old-fashioned effect on the surfaces, and it is applicable on interior surfaces only. And it is anti-fungal, bacterial and viruses on painted surfaces in accordance with JIS Z 2801, HGT 3950 standards.

### Special properties:

- Stylish and elegant.
- Excellent adhesion strength.
- Tintable.
- Good open time (45min to make it easy to the technician to shape the wanted design).
- Long term color stability
- Easy to use.
- Easy to clean.
- Odorless, Mercury-free and Lead-free.
- Environmentally friendly, non-toxic and non-flammable.
- This product is anti-bacterial, fungal, viruses' development on applied paint coats.

### Application:

1. Surfaces must be prepared by scraping and priming with diluted QP Bond.
2. Level surface using two layers of Silky Coat putty.
3. Apply one coat QP Fine paint.
4. Apply one coat Yellow Can vinyl silk tinted to color.
5. Tint QP Lamasat to color compatible with Yellow Can color.
6. Use a suitable tool for desired design.

### Application tools:

- Paint brush
- roller, fabric
- decorative roll
- decorative brush.

**Note:** Do not apply if temperature is below 5°C.

### Package and Storage:

- 1/2kg,1kg in plastic container.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production.

### Technical Data:

<b>Color:</b>	<b>Multicolor</b>
<b>Binder:</b>	<b>Styrene Acrylic Copolymer</b>
<b>Priming:</b>	<b>Base A, B, C of yellow can Eggshell, depending on required color</b>
<b>PH value:</b>	<b>7-9</b>
<b>Opacity:</b>	<b>30-40 m<sup>2</sup>/kg</b>
<b>Drying time:</b>	<b>24 hours, subject to the temperature. According to ASTM D 5895</b>
<b>Solid Content</b>	<b>55%</b>