

## QP.LUCITANTO SPONG

### General Description:

High quality water-based decorative pearl paint (Vinyl acetate ethylene), it is used to create a random velvet effect on walls. It is available in different colors and it is applicable on interior surfaces only. And it is anti-fungal, bacterial and viruses on painted surfaces in accordance with JIS Z 2801, HGT 3950 standards.

### Special properties:

1. Stylish and elegant.
2. Excellent adhesion strength.
3. Tintable.
4. Good open time.
5. Easy to use.
6. Easy to clean.
7. Odorless, Mercury-free and Lead-free.
8. Environmentally friendly, non-toxic and non-flammable.
9. This product is anti-bacterial, fungal, viruses' development on applied paint coats.

### Application:

- Surfaces must be prepared by scraping and priming with diluted QP Bond.
- Level surface using three layers of Silky Coat putty.
- Apply one coat of QP Fine paint.
- Tint QP Lucitanto with a suitable color.
- Apply QP Lucitanto by roll.
- Apply another coat of QP Lucitanto.
- Apply yellow can vinyl matt by a suitable tool for design.
- Consider drying time per coat
- Do not apply if temperature is below 5°C.

### Application tools:

- Stain less steel trowel

- Putty knife.

**Note:** Don't mix QP Lucitanto with any kind of liquid. Use it as it is.

### Package and Storage

- 1kg, 2kg, 4kg in plastic container.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production.

### Technical Data:

Color	Multi-color
Gloss	High Glittering Pearl
Binder	Vinyl acetate ethylene
Priming	Yellow Can vinyl matt
PH value	7-9
Opacity	6-8 m <sup>2</sup> /kg
Drying time	24 hours, subject to temperature. According to ASTM D5895
Solid Content	66%