

QP. DECORAH

General Description:

Interior water-based spraying putty (Vinyl Acetate Copolymer), it is applicable on both old and new surfaces.

Special Features:

1. Elastic properties.
2. High permeability.
3. Easy to spray.
4. Excellent adhesion.
5. Easy to sand after drying.
6. Odorless, Mercury-free and lead-free.
7. Environmentally friendly, non-toxic and non-flammable.

Application steps:

Preparation of surface:

- Scrape the surface well to remove plaster particles, dust, oil... etc.
- Treat all cracks, chips and all damage by using QP. CRACK.
- Surface must be dry when applied.

Priming:

To maintain the surface stability and to achieve the highest adhesion; it is recommended to prime the surfaces, using QP. BOND in a ratio of 1:5 QP. BOND to water.

Application:

- Chose appropriate spraying machines which depend on the size of grains.
- Spray the filler on prepared area.
- Wait 3-5 minutes of drying then use a roll to apply the grains.
- Apply the emulsion after the layer become completely dry.

Note:

- Don't mix putties with any liquid, it is used as it is.
- Do not apply if temperature is below 5° C.

Package & storage:

- 25 kg in plastic bags.
- Must be stored away from direct heat or frost unopened in dry condition, for maximum of 12 month from the date of production.

Technical Data:

Color	White
Binder	Vinyl acetate Copolymer
Specific density	1.7
Drying time	12-24 hours after application, According to ASTM D5895
Solid content	66%
Consumption:	1.6m² /kg