

QP. LUX FONDO

General Introduction:

High quality acrylic base coat (Styrene acrylic copolymer), available in grain or smooth finish. Easily applied for decorative finishes. And it is anti-fungal, bacterial and viruses on painted surfaces in accordance with JIS Z 2801, HGT 3950 standards.

Special features:

1. Excellent adhesion strength.
2. Tint able.
3. Good open time.
4. Easy to use.
5. Odorless, Mercury-free and Lead-free.
6. Environmentally friendly, non-toxic and non-flammable.
7. Easy to clean.
8. This product is anti-bacterial, fungal, viruses' development on applied paint coats.

Application Steps:

1. Preparation of surface:

- Clean dirt, oil, or any foreign matter.
- Treat all cracks, chips and all damage, using QP. Crack.
- Scrape well and remove all dust and loose particles.

2. Priming: To ensure the best possible adhesion, prime using QP. Bond.

3. Plastering: If dealing with uneven surfaces, or very porous substrates, use QP. Silky Coat prior to application.

4. Application:

- Use a brush or roller.
- Stir paint well before applying.
- Apply as many coats as needed considering drying time per coat.
- No dilution before application.

Note: Do not apply if temperature is below 5°C.

Package & Storage:

- 1kg, 5 kg in metal or plastic containers.
- Must be stored away from direct heat or frost, unopened, in a dry location, for a maximum of 12 months from the date of production.

Technical Data:

Color	White
Gloss	Flat, (gm=2.5)
Binder	Styrene Acrylic Copolymer
PH value	8-9
Drying time	1 hour-3, subject to temperature, According to standard specification ASTM D 5895
Film thickness	50 micrometer
Fineness	50 micrometer, According to standard specification ISO1524
Solid content	65 %
Coverage	3-4 m²/1kg

QUDS PAINTS

QUDS PAINTS INDUSTRY LTD .CO

شركة القدس لصناعة الدهانات ذ.م.م

المنطقة الحرفية - سحاب - الاردن 11012 - ص-ب سحاب 176 - هاتف: 0096264029023 - فاكس: 0096264020504
Industrial Zon - Sahab - Jordan 11512 - P.O.Box 176 - Tel: 0096264029023 - Fax : 009624020504